

KEY FEATURES:

- Interactive Board embedded. Pointer, Pen, and Annotation software included. Even white wall can be used for presentation with annotation!
- Auto Vertical digital keystone correction & Auto Ceiling function.
- Super Wide Angle Lens (100" at 2 m) with Zoom 1.2 : 1.
- True XGA resolution. SXGA, SVGA, and VGA.
- Smart data compression / expansion, and video scaling.
- Accepts Composite, S, and Component Video in all major standards.



LC-XIP2000

2000 ANSI Lumens!
LCD XGA Interactive Projector

NO EXTRA DEVICE REQUIRED FOR...

Remark and annotation during presentation

Interactive learning software control at schools

...AND MORE!

SPECIFICATIONS : XIP-2000

Screen Brightness.....	2000 ANSI Lumens
Illumination Uniformity.....	85%
Contrast Ratio.....	400:1
Projection Lamp.....	200 W
Estimated Lamp Life.....	2000 hours (Eco)
Imaging System.....	0.63" Ply-silicon TFT Active Matrix type
Screen Pixels.....	1024x768
Total Pixels.....	2,359,296 ((1024x768)x3)
Lens Type.....	Manual Zoom and Focus
Lens Specs.....	Speed: f1.6~1.88; FL: 18.6~22.3mm
Lens Ratios.....	Zoom Range: 1.2:1
Image Diagonal.....	40~300 in (50~150 in*)
Image Width.....	0.81~6.1 m (1.0~3.0 m*)
Throw Distance.....	0.8~6.2 m
Front Elevation.....	up to 14° up
Lens Shift (U/D ratio).....	9 : 1
Vertical Keystone Correction.....	Digital: up to 30° up or down or Auto
Scanning Frequency.....	Auto: H Sync. 15~69 kHz; V Sync. 43~85 Hz
Dot Clock.....	110 MHz
Image Orientation.....	Normal, Reversed, Inverted
Local Control / Power Management.....	Full Function / Auto Shut-Off
Remote Projector Control.....	Wireless (Infra Red) x 1
Computer Native Resolution.....	1024x768 (XGA)
Computer: Compatibility.....	SXGA (compressed), XGA, SVGA and VGA & MAC
Computer: Formats.....	1280x1024, 1024x768, 800x600, 640x480
Fan Noise.....	41 dBA (Standard)

*Recommended screen size for using interactive function.

Video Compatibility.....	NTSC / PAL / SECAM / NTSC 4.43 / PAL-M&N
Video HD Compatibility.....	480i/p, 540p, 576i/p, 720p, 1035i, 1080i
Formats Support.....	Normal 4:3 and Wide Screen 16:9
Video: Image Sizing.....	Video Scaling Technology
RS-232 Control Port.....	Mini DIN 8 Pin x 1 (Serial)
Signal I/O:	
1. Computer IN 1.....	HD15 x 1
2. Computer IN 2 / Component IN.....	HD15 x 1
3. Computer OUT.....	HD15 x 1
4. Composite.....	RCA x 1
5. S-Video.....	Mini DIN-4 x 1
Audio Inputs.....	Mini-jack (stereo) x1 (with variable)
Audio Outputs.....	Mini-jack (stereo) x1 (with variable)
Mouse Control port.....	USB type B x1
Audio: Amplifier.....	Mono: 2 Watt
Audio: Built In Speaker.....	40 x 30 mm oval x 1
Cabinet Size (HxWxD).....	.96 x 310 x 270 mm
Weight.....	3.3 kg
Packaged Size (HxWxD).....	250 x 410 x 520 mm
Packaged Weight.....	TBA
Power Requirements.....	100-240V AC, 50/60Hz
Power Consumption.....	250W (Standard), 210W (Eco), 2W (Stand-by)
Power Cord.....	Detachable
Security Facilities.....	Kensington® Security Slot
Operating Temperature.....	5~35°C
User Maintenance.....	Clean Air Intake, Replace Lamp

INCLUDED ACCESSORIES:

Owner's Manual (CD-ROM). Quick Start Guide. VGA Computer Input Cable. AC cord. S-Video Cable. RCA Video Cable. Phone Jack Audio Cable. USB Cable. Wireless Remote Control. Filter. Pointer. Pen.

OPTIONAL ACCESSORIES:

Replacement Lamp. Soft Carry Case. RS232 Cable. Filter. 5M USB Extension Cable. 5V/500mA Power Adapter for USB Extension Cable. Pointer. Pen.

I/O TERMINAL:

